

# CHeKT 15W IP Horn Outdoor Speaker

Available Model:  
**CKIPS15W**



## 15 Watt IP Speaker

Combine video & audio systems into a single proactive security solution.

Use the CHeKT outdoor speaker to provide up to 113 decibel crystal clear announcements. This speaker connects to your network with a single LAN cable for POE and network communications — allowing you to combine video and audio systems into a single proactive security solution. Once configured with CHeKT, you can remotely communicate with locations, respond immediately to emergency situations with live announcements or schedule prerecorded messages. Utilizing automated rules, prerecorded messages can be prioritized to broadcast right away.

## Product Features

### IP67 Waterproof Design



For installation  
in outdoor settings

### Sound Projection



Produces loud and  
excellent sound quality

### Multi-Compatibility



Compatible with VoIP,  
SIP devices (IPPBX, IP Phone)  
via SIP

### VMS Compatible



Compatible with  
IP Camera VMS via ONVIF

### Pre-recorded Messages



Speaker supports  
pre-recorded messages

### HTTP API Support

HTTP

Support HTTP API  
for alarm in transmit

# Specification

<b>Audio</b>	
Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
<b>Speaker</b>	
Max SPL	113dB
Frequency response	300Hz~8KHz
Frequency Range	500-2KHZ ± 10dB 400-12KHZ ± 20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB
<b>Network</b>	
Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA
<b>Amplifier</b>	
Amplifier Description	Built-in 15W Amplifier
<b>Alarm</b>	
Alarm Input	1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.
<b>General</b>	
Operating Temperature	-30°C ~ +60°C
Operating humidity	5%~85%
Material	ABS (IP67 water-proof)
Rate Power	15W
Power Supply	POE or DC12V~24V
Installation	Wall Mounted
Dimensions	285 x 205 x 290 mm
Net Weight	1.3 KG
Languages	English
Warranty	2 years
Package Includes	Network Horn Speaker User Manual

Specifications & designs are subject to change without prior notice.